

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

PPB, 125-225mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



| | |
|----------------------------|--------------------|
| Declaration Number: | L0029-02-CE |
|----------------------------|--------------------|

| | |
|-----------------------|---|
| Intended Use: | Slip tie for connecting a new masonry leaf to an existing structure whilst allowing in-plane movement. |
| Notified Body: | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| | |
|--|--------------------|
| Essential Characteristics | |
| Shear Load Capacity: | 1990N |
| Capacities given for: | |
| Overall Wall Tie Length: | 125mm-225mm |
| Design Cavity Width: | 10mm |
| Minimum Embedment Depth: | 100mm |
| Minimum Mortar Joint Thickness: | 10mm |
| Minimum Mortar Class: | Type M4 |
| Displacement at 1/3 Load Capacity | |
| In shear: | 0.32 |

DECLARATION OF PERFORMANCE

| | |
|-----------------------------|-------------------|
| Failure Modes: | |
| In shear: | Rotation of cramp |
| Recommended Spacing: | As required |
| Durability | |
| Material Coating Reference: | 3 |
| Steel Grade: | 1.4301/1.4401 |
| Dangerous Substance | None |

Signed for and on behalf of the manufacturer by



Rune Magnusson
Managing Director Europe West & APAC
1st April 2022

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom