

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Staifix Frame Tie, 115mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0002-01-NI
---------------------	-------------

Intended Use:	Shear tie for connecting a new masonry leaf to an existing structure.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Tensile Load Capacity:	1560N
Shear Load Capacity:	720N
Capacities given for:	
Overall Wall Tie Length:	115mm
Design Cavity Width:	0mm
Embedment Depth:	75mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In tension:	0.25
In shear:	0.52
Failure Modes:	
In tension:	Straightening of tie
In shear:	Rotation / bending of tie
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Managing Director Europe West & APAC
 1st April 2022

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom