

CI/SfB	(21.9)	Xt6	
April 2023			

Compatible with designs to
BS EN 1992-1-1:2004 (EC2)



Ancon[®]
**Reinforcement
Continuity Systems**
for the Construction Industry



We are one team. **We are Leviat.**

Leviat is the new name of CRH's construction accessories companies worldwide.

Under the Leviat brand, we have united the expertise, skills and resources of Ancon and its sister companies to create a world leader in fixing, connecting and anchoring technology.

The products you know and trust will remain an integral part of Leviat's comprehensive brand and product portfolio. As Leviat, we can offer you an extended range of specialist products and services, greater technical expertise, a larger and more agile supply chain and better, faster innovation.

By bringing together CRH's construction accessories family as one global organisation, we are better equipped to meet the needs of our customers, and the demands of construction projects, of any scale, anywhere in the world.

This is an exciting change. Join us on our journey.

Read more about Leviat at [Leviat.com](https://www.leviat.com)



Our product brands include:

Ancon[®]

HALFEN

HELIFIX

ISEDIO

PLAKA



60

locations

sales in
30+
countries

3000

people worldwide

Imagine. Model. Make.

Leviat.com

Eazistrip

Continuity of Reinforcement at Construction Joints

The use of reinforcement continuity systems is a widely accepted means of providing continuity of reinforcement across construction joints in concrete.

The Eazistrip system comprises a galvanised steel casing which houses pre-bent bars. The unit is cast into the face of a concrete wall and the bars are straightened, ready for lapping when required.



Leviat manufactures other Ancon CARES-approved reinforcement continuity systems for use when bar diameters exceed 16mm, lap lengths do not fit within an Eazistrip box and on-site bar straightening is keen to be avoided.


KSN Anchors

Ancon KSN threaded anchors are supplied fixed to a timber carrier and used in conjunction with Bartec Plus parallel threaded reinforcing bars. There is no on site bar straightening and virtually no restriction on bar length, so EC2 lap lengths are easily accommodated. KSN Anchors minimise rebar congestion in the wall and are suitable for bar diameters up to 20mm.



Coupler Box

Ancon Couplers, supplied fixed to an Eazistrip-style galvanised steel casing, are used in combination with Ancon CXL parallel threaded reinforcing bars. There is no on site bar straightening and virtually no restriction on bar length, so EC2 lap lengths are easily accommodated. U-bars join two rows of couplers to the same box, accelerating the speed of installation.



Coupler Strip

Ancon Couplers can also be supplied fixed to a steel strip to simplify rebar continuity at joints where walls are curved on plan. The flexible strip is nailed directly to the curved shuttering.

Starter Bars

This system consists of a Starter Bar supplied fixed to an Ancon coupler, normally the TT Tapered Thread Coupler, and a threaded continuation bar. The standard range suits bar diameters up to 32mm.

Contents

Eazistrip	4
Standard Range Configurations	5
Standard Range Specifications	6-7
Installation	8
On-site Cutting	9
Enquiry/Order Form	10
Eazistrip Water Stop	11
Other Ancon Products	11



Suitable for BS 8110 and EC2 Designs



EC2 Indented Construction Joint



No Drilling of Formwork



Corrosion-Resistant Galvanised Casing



Dimpled Surface Provides Key




ISO 9001, ISO 14001 & OHSAS 18001



Technical Approval TA 5017

Eazistrip Reinforcement Continuity Systems



Eazistrip Reinforcement Continuity Systems

The Eazistrip Reinforcement Continuity System is a quick and easy-to-install method of maintaining continuity of reinforcement at construction joints in concrete. It consists of a galvanised steel casing with a dimpled surface to provide an effective concrete bond. Pre-bent bars are housed within the casing and are enclosed by a protective heavy duty plasticised cardboard cover. Each end of the unit is sealed with a polystyrene block in order to prevent the ingress of concrete.

The complete unit is nailed to the formwork. Alternatively it can be wired back to the main reinforcement cage. The concrete is then cast. After striking the formwork, the cover is removed and the bars are straightened, ready for lapping onto the main reinforcement, using an Eazistrip re-bending tool.

The steel casing remains embedded in the wall and is filled with concrete when the next section is poured, the dimpled surface providing an efficient key.

Use of the Eazistrip system offers many benefits over conventional joint construction, including the simplification of formwork design and removal of the need to drill shuttering.

This contributes to the acceleration of the construction process. As the bars remain enclosed within the casing until required, they are protected and the risk of injury from projecting bars is minimised. Easy to use, the system requires little on site training in order to carry out installation.

The Eazistrip system is potentially suitable for use in any construction joint in concrete, but the most commonly found applications include:

- Floor slabs
- Walls
- Stairwells
- Corbels
- Diaphragm walls
- Jumpforms
- Brick support ledges

Quality Assurance

Eazistrip Reinforcement Continuity Systems are manufactured using CARES approved bar. The type of reinforcement is selected by us to provide a suitable degree of ductility, ensuring that it complies with the tensile requirements of BS4449: 2005 Grade B500C after prefabrication and re-bending on site. The bars are bent in accordance with BS8666: 2005.

It is the designer's responsibility to ensure reinforcement is adequately designed in accordance with the code and detailed to ensure anchorages and bearing stresses are appropriate. Ancon Ltd trading as Leviat is a BS EN ISO 9001 registered company.


Ancon Eazistrip is approved by UK CARES.




Eazistrip Reinforcement Continuity Systems are suitable for use with designs undertaken in accordance with BS EN 1992-1-1: 2004 (Eurocode 2) and BS 8110-1: 1997.

Standard Range Configurations


Type 80




Type 110H




Type 110U




Type 140




Type 160





Type 190



Type 240




When the stirrup width exceeds 220mm, units will be supplied as two single overlapping hooks, to be positioned side by side.



1200mm

150mm*
Centres



1200mm

200mm*
Centres

*Other centres are available


Notes: Units containing 16mm bars are nominally 50mm deep. On 16mm Ø Type U boxes, the stirrup may be achieved using two shape code 21 bars. These are referenced DH.

Eazistrip Reinforcement Continuity Systems

Standard Range Specifications

The following tables give details of the Eazistrip standard ranges. Many customers require purpose made units to suit their particular application. In order to meet this requirement Leviat will manufacture according to your specific bar arrangement. The most common shapes are shown on page 10. For further details please contact us.

U Type Box Dimensions



UK Range Dimensions

Part No.	Box Width mm	Box Length mm	Rebar Dia mm	Centres mm	Stirrup Height (h) mm	Stirrup Width (b) mm	Leg Length (l) mm	Bars / Box
EZ 80H 10/200	80	1200	10	200	170	60	410	6
EZ 80H 12/150	80	1200	12	150	170	80	500	8
EZ 80H 12/200	80	1200	12	200	170	80	500	6
EZ 110U 10/150	110	1200	10	150	170	90	410	8
EZ 110U 10/200	110	1200	10	200	170	90	410	6
EZ 110U 12/200	110	1200	12	200	170	90	500	6
EZ 110H 16/150	110	1200	16	150	170	96	640	8
EZ 110H 16/200	110	1200	16	200	170	96	640	6
EZ 140U 10/150	140	1200	10	150	170	120	410	8
EZ 140U 10/200	140	1200	10	200	170	120	410	6
EZ 140U 12/150	140	1200	12	150	170	120	500	8
EZ 140U 12/200	140	1200	12	200	170	120	500	6
EZ 160U 10/150	160	1200	10	150	170	140	410	8
EZ 160U 10/200	160	1200	10	200	170	140	410	6
EZ 160U 12/150	160	1200	12	150	170	140	500	8
EZ 160U 12/200	160	1200	12	200	170	140	500	6
EZ 160DH 16/150	160	1200	16	150	170	140	640	16
EZ 160DH 16/200	160	1200	16	200	170	140	640	12
EZ 190U 10/150	190	1200	10	150	170	170	410	8
EZ 190U 10/200	190	1200	10	200	170	170	410	6
EZ 190U 12/150	190	1200	12	150	170	170	500	8
EZ 190U 12/200	190	1200	12	200	170	170	500	6
EZ 190DH 16/150	190	1200	16	150	170	170	650	16
EZ 190U 16/200	190	1200	16	200	170	170	650	6
EZ 240U 10/150	240	1200	10	150	170	220	410	8
EZ 240U 10/200	240	1200	10	200	170	220	410	6
EZ 240U 12/150	240	1200	12	150	170	220	500	8
EZ 240U 12/200	240	1200	12	200	170	220	500	6
EZ 240U 16/150	240	1200	16	150	170	220	650	8
EZ 240U 16/200	240	1200	16	200	170	220	650	6

Notes: Those sizes shown in **bold** are normally available from stock. Dimensions shown in the above table are nominal. Heights and lengths may typically vary by one bar diameter. Maximum box length is 3m dependant upon weight. Boxes with a DH reference contain double hook bars rather than a single U bar. Units containing 16mm bars are nominally 50mm deep (d).

UK Range Load Capacities

For transverse shear load capacities of the standard Eazistrip range in C32/40 grade concrete, please refer to the following table. For load capacities outside of this range please contact us.

Effective Depth d (mm)	Transverse Shear Capacity, V_{Rd} (kN/m) for Concrete Grade C32/40								
	80	100	120	140	160	180	200	220	240
	EZ 80H	EZ 80H	EZ 110U/H	EZ 140U	EZ 160U/DH	EZ 160U/DH	EZ 190U/DH	EZ 240U	EZ 240U
Rebar Diameter / Spacing (mm)	10/200	48.1	56.0	67.2	78.4	89.6	95.8	95.8	95.8
	10/150	52.9	61.4	69.4	78.4	89.6	100.8	112.0	118.9
	12/200	-	63.0	71.2	78.9	89.6	100.8	112.0	118.9
	12/150	-	69.4	-	86.8	94.9	102.6	112.0	118.9
	16/200	-	-	86.2	-	104.4	112.9	121.2	126.1
16/150	-	-	94.9	-	114.9	124.3	133.4	138.8	144.0

Continental Range Dimensions

Part No.	Box Width mm	Box Length mm	Rebar Dia mm	Centres mm	Stirrup Height (h) mm	Stirrup Width (b) mm	Leg Length (l) mm	Bars / Box
EZ 80H 10/150	80	1200	10	150	155	60	340	8
EZ 80H 10/200	80	1200	10	200	155	60	340	6
EZ 80H 12/150	80	1200	12	150	155	80	405	8
EZ 80H 12/200	80	1200	12	200	155	80	405	6
EZ 110H 16/150	110	1200	16	150	155	96	575	8
EZ 110H 16/200	110	1200	16	200	155	96	575	6
EZ 110U 10/150	110	1200	10	150	155	90	340	8
EZ 110U 10/200	110	1200	10	200	155	90	340	6
EZ 110U 12/150	110	1200	12	150	155	90	340	8
EZ 110U 12/200	110	1200	12	200	155	90	405	6
EZ 140U 10/150	140	1200	10	150	155	120	340	8
EZ 140U 10/200	140	1200	10	200	155	120	340	6
EZ 140U 12/150	140	1200	12	150	155	120	405	8
EZ 140U 12/200	140	1200	12	200	155	120	405	6
EZ 160U 10/150	160	1200	10	150	155	140	340	8
EZ 160U 10/200	160	1200	10	200	155	140	340	6
EZ 160U 12/150	160	1200	12	150	155	140	405	8
EZ 160U 12/200	160	1200	12	200	155	140	405	6
EZ 160DH 16/150	160	1200	16	150	160	140	410	16
EZ 160DH 16/200	160	1200	16	200	160	140	410	12
EZ 190U 10/150	190	1200	10	150	155	170	340	8
EZ 190U 10/200	190	1200	10	200	155	170	340	6
EZ 190U 12/150	190	1200	12	150	155	170	405	8
EZ 190U 12/200	190	1200	12	200	155	170	405	6
EZ 190DH 16/150	190	1200	16	150	160	170	575	16
EZ 190U 16/200	190	1200	16	200	160	170	650	6
EZ 240U 10/150	240	1200	10	150	155	220	340	8
EZ 240U 10/200	240	1200	10	200	155	220	340	6
EZ 240U 12/150	240	1200	12	150	155	220	500	8
EZ 240U 12/200	240	1200	12	200	155	220	500	6
EZ 240U 16/150	240	1200	16	150	160	220	650	8
EZ 240U 16/200	240	1200	16	200	160	220	650	6

Notes: Dimensions shown in the above table are nominal. Heights and lengths may typically vary by one bar diameter. Maximum box length is 3m dependant upon weight. Boxes with a DH reference contain double hook bars rather than a single U bar. Units containing 16mm bars are nominally 50mm deep (d).


Radiused Eazistrip

Many of the units detailed in the brochure are available radiused. Please contact us with your requirements.




Eazistrip Reinforcement Continuity Systems


Installation




Nail the Eazistrip through the casing to the formwork or alternatively securely tie the projecting anchorage reinforcing bars back to the main reinforcement. In both cases the Eazistrip box should be securely fixed to avoid displacement during concreting. The casing should be tight against the formwork. Pour concrete.



Strike the formwork to reveal the cover.



Remove the cover to expose the pre-bent bars.




Straighten the bars using the appropriate sized Ancon Eazistrip re-bending tool for the size of bar. The bars should be straightened only once. To avoid damage to adjacent concrete, it is prudent to allow a concrete curing period of seven days. See 'Bar Straightening' for more information.



Once the bars are straightened and aligned they are ready for lapping with the concrete element reinforcement, provided by others.

Bar Straightening

The bars in the Eazistrip box must be straightened using the appropriate sized Ancon Eazistrip re-bending tool. This is a steel tube designed to fit over the bar, the internal diameter being slightly larger than the maximum dimension over the ribs of the bar. One end of the tube has a section cut away; this provides support to the outside of the bend during straightening of the bar and limits the point contact of the tube on the bar.



Use of the tool allows the re-bending process to be carried out in a smooth continuous action (avoiding jerky action), the tube being moved along the bar and around the bend as it is straightened. Scaffold tubes or similar must not be used to straighten bar.

To enable the re-bending tool to be fitted onto the bar, the bar should be pulled the minimum distance from the Eazistrip steel casing to enable this. The re-bending tool should then be slid along the bar to the start of the bend radius.

The bar straightening process should be smooth and progressive with the tube allowed to move along the bend towards the metal casing as it is straightened. The tool should contact the Eazistrip steel casing at the completion of the straightening process.

The tube is then removed and the straightened bar checked for alignment and cover with the adjoining reinforcement.

The Eazistrip reinforcing bars should not be straightened when the temperature of the steel is below 5°C. Where straightening is necessary below 5°C, indirect warming of the steel to a temperature not exceeding 100°C is permitted.


The use of scaffold tubes, or other inappropriate tools will result in excessive kinks in the region of the bar bend and result in undesirable work hardening which may damage the bar and affect the strength of the bar. Re-bending must be undertaken using only the Ancon Eazistrip re-bending tool. Bending the bar in excess of the recommendations will also result in work hardening of the rebar and should therefore be avoided.



Scan the code to watch an installation video.


On-Site Cutting

1




Identify the location of the intended cut.

2




Slide the protective cover from the box and remove the bars which pass over the cut location.

3



Cut through the steel casing using a disc cutter.

4



Replace the bars to face the opposite direction to their original position. Cut the cover to the same lengths as the steel casing and replace to protect the bars. The ends of the boxes must be sealed, using polystyrene blocks, to prevent the ingress of concrete.

Note: Protective gloves should be worn when removing covers, straightening bars, cutting boxes and during general handling of Eazistrip.



Eazistrip Water Stop

Where the potential for water ingress through the construction joint is a major concern, Eazistrip can be supplied with a Pentaflex hydrostatic seal. The seal is factory fitted inside and outside the box to provide double-sided protection against water or moisture permeation along the joint face.

As Pentaflex is a hydrostatic seal, it is not reliant on expansion, unlike hydrophilic type seals, and it provides a continuous elastic seal by means of the bond between the Pentaflex and the fresh concrete. Resistant to organic waste water, Pentaflex has been tested by the Hygiene-Institut, Geisenkirchen, Germany for use with potable water.

A protective film on the Pentaflex prevents contamination by dust or dirt during storage, handling and installation. The film must be removed prior to concreting. When installing and abutting boxes, joints are achieved by pressing together a 50mm overlap of the Pentaflex material, to ensure continuous protection against water permeation.



Other Ancon Products

Reinforcing Bar Couplers

The use of reinforcing bar couplers can provide significant advantages over lapped joints. Design and construction of the concrete can be simplified and the amount of reinforcement required can be reduced. The Ancon range includes parallel-threaded, tapered-threaded, mechanically bolted and grouted couplers.



Shear Load Connectors

Ancon DSD Shear Load Connectors are used to transfer shear across expansion and contraction joints in concrete. They are more effective at transferring load and allowing movement to take place than plain dowels, and can be used to eliminate double columns at structural movement joints in buildings.



Channel and Bolt Fixings

Leviat offers a wide range of Ancon channels and bolts in order to fix stainless steel masonry support, restraints and windposts to structural frames. Cast-in channels and expansion bolts are used for fixing to the edges of concrete floors and beams.



Insulated Balcony Connectors

Our thermally insulated connectors minimise heat loss at balcony locations while maintaining structural integrity. They provide a thermal break and, as a critical structural component, transfer moment, shear, tension and compression forces. Standard solutions are available for concrete-to-concrete, steel-to-concrete and steel-to-steel interfaces.



Punching Shear Reinforcement

Ancon Shearfix is used within a slab to provide additional reinforcement from punching shear around columns. The system consists of double-headed steel studs welded to flat rails and is designed to suit the load conditions and slab depth at each column using our free calculation software.



Special Stainless Steel Fabrications

We have a wealth of experience working with different types and grades of stainless steel. Leviat's advanced manufacturing facilities enable one-off or volume orders to be fabricated to individual project requirements and to exacting quality standards. Considerable material stocks are maintained in order to meet urgent delivery deadlines.





Leviat[®]
A CRH COMPANY

Innovative engineered products and construction solutions that allow the industry to build safer, stronger and faster.



Worldwide contacts for Leviat:

Australia

Leviat
98 Kurrajong Avenue,
Mount Druitt Sydney, NSW 2770
Tel: +61 - 2 8808 3100
Email: info.au@leviat.com

Austria

Leviat
Leonard-Bernstein-Str. 10
Saturn Tower, 1220 Wien
Tel: +43 - 1 - 259 6770
Email: info.at@leviat.com

Belgium

Leviat
Industrielaan 2
1740 Ternat
Tel: +32 - 2 - 582 29 45
Email: info.be@leviat.com

China

Leviat
Room 601 Tower D, Vantone Centre
No. A6 Chao Yang Men Wai Street
Chaoyang District
Beijing · P.R. China 100020
Tel: +86 - 10 5907 3200
Email: info.cn@leviat.com

Czech Republic

Leviat
Business Center Šafránková
Šafránková 1238/1
155 00 Praha 5
Tel: +420 - 311 - 690 060
Email: info.cz@leviat.com

Finland

Leviat
Vädursgatan 5
412 50 Göteborg / Sweden
Tel: +358 (0)10 6338781
Email: info.fi@leviat.com

France

Leviat
6, Rue de Cabanis
FR 31240 L'Union
Toulouse
Tel: +33 - 5 - 34 25 54 82
Email: info.fr@leviat.com

Germany

Leviat
Liebigstrasse 14
40764 Langenfeld
Tel: +49 - 2173 - 970 - 0
Email: info.de@leviat.com

India

Leviat
309, 3rd Floor, Orion Business Park
Ghodbunder Road, Kapurbawdi,
Thane West, Thane,
Maharashtra 400607
Tel: +91 - 22 2589 2032
Email: info.in@leviat.com

Italy

Leviat
Via F.lli Bronzetti 28
24124 Bergamo
Tel: +39 - 035 - 0760711
Email: info.it@leviat.com

Malaysia

Leviat
28 Jalan Anggerik Mokara 31/59
Kota Kemuning, 40460 Shah Alam
Selangor
Tel: +603 - 5122 4182
Email: info.my@leviat.com

Netherlands

Leviat
Oostermaat 3
7623 CS Borne
Tel: +31 - 74 - 267 14 49
Email: info.nl@leviat.com

New Zealand

Leviat
2/19 Nuttall Drive, Hillsborough,
Christchurch 8022
Tel: +64 - 3 376 5205
Email: info.nz@leviat.com

Norway

Leviat
Vestre Svanholmen 5
4313 Sandnes
Tel: +47 - 51 82 34 00
Email: info.no@leviat.com

Philippines

Leviat
2933 Regus, Joy Nostalg,
ADB Avenue
Ortigas Center
Pasig City
Tel: +63 - 2 7957 6381
Email: info.ph@leviat.com

Poland

Leviat
Ul. Obornicka 287
60-691 Poznań
Tel: +48 - 61 - 622 14 14
Email: info.pl@leviat.com

Singapore

Leviat
14 Benoi Crescent
Singapore 629977
Tel: +65 - 6266 6802
Email: info.sg@leviat.com

Spain

Leviat
Polígono Industrial Santa Ana
c/ Ignacio Zuloaga, 20
28522 Rivas-Vaciamadrid
Tel: +34 - 91 632 18 40
Email: info.es@leviat.com

Sweden

Leviat
Vädursgatan 5
412 50 Göteborg
Tel: +46 - 31 - 98 58 00
Email: info.se@leviat.com

Switzerland

Leviat
Grenzstrasse 24
3250 Lyss
Tel: +41 - 31 750 3030
Email: info.ch@leviat.com

United Arab Emirates

Leviat
RA08 TB02, PO Box 17225
JAFZA, Jebel Ali, Dubai
Tel: +971 (0)4 883 4346
Email: info.ae@leviat.com

United Kingdom

Leviat
President Way, President Park,
Sheffield, S4 7UR
Tel: +44 - 114 275 5224
Email: info.uk@leviat.com

United States of America

Leviat
6467 S Falkenburg Rd.
Riverview, FL 33578
Tel: (800) 423-9140
Email: info.us@leviat.us

For countries not listed

Email: info@leviat.com

Leviat.com

Notes regarding this catalogue

© Protected by copyright. The construction applications and details provided in this publication are indicative only. In every case, project working details should be entrusted to appropriately qualified and experienced persons. Whilst every care has been exercised in the preparation of this publication to ensure that any advice, recommendations or information is accurate, no liability or responsibility of any kind is accepted by Leviat for inaccuracies or printing errors. Technical and design changes are reserved. With a policy of continuous product development, Leviat reserves the right to modify product design and specification at any time.



For more information on these products, contact:

Leviat

President Way
President Park
Sheffield, S4 7UR
United Kingdom

Tel: +44 (0) 114 275 5224
Fax: +44 (0) 114 276 8543

Email: info.ancon.uk@leviat.com

For sales and technical enquiries:
Email: reinforcement.uk@leviat.com

www.ancon.co.uk
www.leviat.com