

Declaration Number: A0056-00-EN

Declaration of Performance

ANCON hereby declares that the product range identified as,

CCB3-100

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as a,

Asymmetrical Wall Tie covered in clause 1 of the standard

Intended Use: Type 3 wall tie for connecting cellular clay thin-joint

blockwork to a traditional masonry leaf. Suitable for a

100mm cavity.

Notified Body: CERAM Research Limited

Queens Road, Penkhull STOKE-ON-TRENT ST4 7LQ

United Kingdom

Tel: +44 (0)1782 764444

Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity: 880N
Tensile Load Capacity: 1320N

Water Shedding Capability: Resistant

Durability: Material/coating reference 3, Steel grade 1.4301

Dangerous Substances: None

Conditions

Embedment Depth: Cellular Clay Block 70mm/Traditional 62.5mm

Minimum Mortar Class: Thin-Joint Mortar/Traditional Type M2 (iv)

Minimum Mortar Joint Width: Cellular Clay Block 1mm/Traditional 10mm

Recommended Spacing: Refer to Ancon technical literature

Manufactured by:



Ancon Building Products

President Way President Park Sheffield S4 7UR United Kingdom

Tel: +44 (0)114 275 5224 Fax: +44 (0)114 276 8543 Email: info@ancon.co.uk Web: www.ancon.co.uk Twitter: @AnconUK Authorised by:

Stuart Maxwell, Managing Director, on 5th August 2014

S apres O