

We hereby declare that the product identified as,

AMR/S/D3.5/W150

conforms to the provisions of BS EN 845-3:2013+A1:2016, as **Bed Joint Reinforcement defined in 4.2.2 of the Standard**

Intended Use: **For structural uses in walls and partitions**

Approved Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom

Approved Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Product Dimensions

Length:	2700 ±1.5%
Width:	150 ±5mm
Profile Height:	2.9 ±0.4mm
Longitudinal Wire Size:	3.93 ±0.1mm
Cross Wire Size:	2.30 ±0.1mm
Pitch of Cross Wires:	450 ±3.0%

Performance

Characteristic Yield Strength of Longitudinal Wires:	500N/mm²
Characteristic Yield Strength of Cross Wires:	500N/mm²
Bond Strength:	6568N
Bond Length:	450mm
Anchorage Length:	450mm
Shear Load Capacity of Welds:	2300N
Mortar Class:	General purpose ≥ M4
Masonry Units:	fb ≥ 5 N/mm²
Ductility:	Normal

Durability

Durability - Material/Coating Reference: **R3 (Stainless Steel)**

Dangerous Substances: **None**

Authorised by:



Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

Leviat

A CRH COMPANY

Ancon Ltd trading as Leviat
President Way
President Park
Sheffield S4 7UR
United Kingdom

+44 (0)114 275 5224
info.ancon.uk@leviat.com
Ancon.co.uk | Leviat.com