

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

AMR/G/D3.5/W100

conforms to the provisions of BS EN 845-3:2013+A1:2016, as Bed Joint Reinforcement defined in 4.2.2 of the Standard.



Declaration Number:	L0226-03-CA
---------------------	-------------

Intended Use:	For structural use in walls and partitions
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Product Dimensions	
Length:	2700 ±1.5%
Width:	100 ±5mm
Profile Height:	2.9 ±0.4mm
Longitudinal Wire Size:	3.93 ±0.1mm
Cross Wire Size:	2.30 ±0.1mm
Pitch of Cross Wires:	450 ±3.0%
Performance	
Characteristic Yield Strength of Longitudinal Wires:	500N/mm ²
Characteristic Yield Strength of Cross Wires:	500N/mm ²
Bond Strength:	3250N

DECLARATION OF PERFORMANCE

Bond Length:	450mm
Anchorage Length:	450mm
Shear Load Capacity of Welds:	2500N
Mortar Class:	General purpose \geq M4
Masonry Units:	$f_b \geq 5$ N/mm ²
Ductility:	Normal
Durability	
Material Coating Reference:	R13 Galvanised Steel
Dangerous Substances:	None

Signed for and on behalf of the manufacturer by



Rune Magnusson
Regional Managing Director, UK & Asia
1st May 2026

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom

Declaration Number: L0226-03-CA