

Page 1 of 2

# Ancon

# **Design Sheet**

## Ancon SPA System

Please provide: contact, project	ct and design details	s.			
Purpose of Your Enquiry	(tick box as approp	riate)			
Quotation required	Specification	Order			
Contact Details					
Contact name					
Company					
Address					
Tel					
Email					
Project Details					
Project name					
Project address					
Order No. (if applicable)					
Typical Application - Shear SPA Frame Cramps Fixed to Sto		Set Screws			0
Wall Ties should be positioned centrally in	0000	1	Dimension B (minimum 20mm)		Angle A
Use Dimension B to achieve this.					
Typical Application - Tension/C			60mm	125mm	-
SPA Frame Cramps Fixed to Sto	eel with M6 Isolated	Set Screws	20mm 7mm    -	_20 mm	Dimension B (minimum 20

### **Design Sheet**

Ancon SPA System

Only Angle A and Dimension B are flexible. Other dimensions are fixed. If other dimensions need to change to suit your application, please contact Leviat's Technical Services Team on 0114 275 5224 for advice.

### **Load Direction - Shear**

Your SPA Reference	Debonding Sleeve Yes or No	Angle A	Dimension B	Applied Load (we will assume 500N SLS if left blank)	Quantity

### **Load Direction - Tension/Compression**

Your SPA Reference	Cavity (from face of angle to inside face of brick)	Angle A	Dimension B	Applied Load (we will assume 500N SLS if left blank)	Quantity