

DECLARATION OF PERFORMANCE

We hereby declare that our,

Load Bearing and Welded Structural Steel Components manufactured from Carbon Steel S355 Angle [Hot rolled], including all support angles, windposts and other bespoke fabrications,

conform to the provisions of Annex ZA, BS EN 1090-1:2009+A1:2011.

System 2+

UK CA

| Declaration Number: L0594-03-CA | |
|---------------------------------|--|
|---------------------------------|--|

Initial inspection and continuous surveillance, assessment and approval of the Factory Production Controls (FPC) is conducted by,

| Approved Body: | BSI Assurance UK Ltd. Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP |
|-------------------------|--|
| Approved Body Number: | 0086 |
| FPC Certificate Number: | 0086 – CPR – 744449 |

| Structural Characteristics | | |
|----------------------------|--|--|
| Load Bearing: | Refer to project file / manufacturing order | |
| Design: | According to EN 1993 (EC3) | |
| Manufacturing: | According to EN 1090-2: Execution Class 2 (EXC2) | |
| Resistance to Fire: | NPD | |
| Fatigue Strength: | NPD | |
| Material Characteristics | | |



Leviat.com



DECLARATION OF PERFORMANCE

| Tolerances on Dimensions: | According to EN 1090-2 | |
|----------------------------|-----------------------------------|--|
| Weldability: | Steel S355J according to EN 10025 | |
| Fracture Toughness: | Minimum 27J at ODegC | |
| Reaction to Fire: | Classified: Class A1 | |
| Release to Cadmium: | NPD | |
| Emission of Radioactivity: | NPD | |
| Durability: | Primed: NPD | |
| Conditions | | |
| | | |

Products/Systems should be stored and installed to the layout drawings and/or other instructions issued by Leviat

Signed for and on behalf of the manufacturer by

Rune Magnusson Managing Director Europe West & APAC 7th November 2023

Manufactured by;

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom



Leviat.com