

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Staifix Starter Tie, 135mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

**UK
CA**

Declaration Number:	L0001-03-CA
---------------------	-------------

Intended Use:	For connecting a new leaf of masonry to an existing structure.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Essential Characteristics	
Tensile Load Capacity:	1360N
Shear Load Capacity:	560N
Capacities given for:	
Overall Wall Tie Length:	135mm
Design Cavity Width:	20mm
Embedment Depth:	75mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In tension:	0..23
In shear:	0.75
Failure Modes:	
In tension:	Pull out of plug end
In shear:	Deformation of tie
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 1st May 2026

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom