

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SDB, 125-150mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0024-05-CA
---------------------	-------------

Intended Use:	Frame cramp for connecting a new masonry leaf to an existing structure. Suitable for cavities from 45mm to 94mm.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	1640N
Compressive Load Capacity (design cavity):	2270N
Tensile Load Capacity (cavity):	3070N
Capacities given for:	
Overall Wall Tie Length:	100-150mm
Design Cavity Width:	45-94mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In Compression:	0.83
In Tension:	0.3
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Pull-out of tie
Water Shedding Capacity:	Resistant
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



Rune Magnusson
Managing Director Europe West & APAC
7th October 2025

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom