

We hereby declare that the product range identified as,

SD38, 300mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

Intended Use: **Wall tie for use with the Ancon 38/17 channel system to connect a new masonry leaf to an existing structure. Suitable for 220-245mm cavities.**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity (cavity +15mm):	650N
Compressive Load Capacity (design cavity):	1790N
Tensile Load Capacity (at min. embedment):	1100N

Capacities given for:

Overall Wall Tie Length:	300mm
Design Cavity Width:	220-245mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

Displacement at 1/3 Load Capacity

In compression:	0.22
In tension:	0.19

Failure Modes:

In compression:	Bending of tie
In tension:	Pull-out of tie

Water shedding capacity:	Resistant
Recommended spacing:	As required

Durability

Material Coating Reference:	3
Steel Grade:	1.4301/1.4401

Dangerous Substance	None
----------------------------	-------------

Authorised by:



Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

Leviat
A CRH COMPANY

Ancon Ltd trading as Leviat
President Way
President Park
Sheffield S4 7UR
United Kingdom

+44 (0)114 275 5224
info.ancon.uk@leviat.com
Ancon.co.uk | Leviat.com