

We hereby declare that the product range identified as,

# SD40, 300mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

Intended Use: **Wall tie for use with the Ancon 40/25 channel system to connect a new masonry leaf to an existing structure. Suitable for 220-245mm cavities.**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom  
Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

## Essential Characteristics

Compressive Load Capacity (cavity +15mm):	<b>650N</b>
Compressive Load Capacity (design cavity):	<b>1790N</b>
Tensile Load Capacity (at min. embedment):	<b>1100N</b>

## Capacities given for:

Overall Wall Tie Length:	<b>300mm</b>
Design Cavity Width:	<b>220-245mm</b>
Minimum Embedment Depth:	<b>50mm</b>
Minimum Cover to Face of Wall:	<b>20mm</b>
Minimum Mortar Joint Thickness:	<b>10mm</b>
Minimum Mortar Class:	<b>Type M2</b>

## Displacement at 1/3 Load Capacity

In compression:	<b>0.22</b>
In tension:	<b>0.19</b>

## Failure Modes:

In compression:	<b>Bending of tie</b>
In tension:	<b>Pull-out of tie</b>

<b>Water shedding capacity:</b>	<b>Resistant</b>
<b>Recommended spacing:</b>	<b>As required</b>

## Durability

Material Coating Reference:	<b>3</b>
Steel Grade:	<b>1.4301/1.4401</b>

<b>Dangerous Substance</b>	<b>None</b>
----------------------------	-------------

Authorised by:



Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

**Leviat**  
A CRH COMPANY

Ancon Ltd trading as Leviat  
President Way  
President Park  
Sheffield S4 7UR  
United Kingdom

+44 (0)114 275 5224  
info.ancon.uk@leviat.com  
Ancon.co.uk | Leviat.com