



# Declaration of Performance

Declaration Number: A0095-01-EN

ANCON hereby declares that the product range identified as,

## FHR 100mm/140mm

conforms to the provisions of,

**ZA Annex, EN 845-1: 2003 +A1: 2008**

as an,

**Internal Head Restraint covered in clause 1 of the standard**

Intended Use:

Internal head restraint for connecting the top of a new masonry wall to the underside of a structural frame - max. 25mm gap

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance.

### Essential Characteristics

Shear Load Capacity:	<b>2079N</b>
Durability:	<b>Material/coating reference 3, Steel grade 1.4301/1.4401</b>
Dangerous Substances:	<b>None</b>

### Conditions

Minimum Mortar Class:	<b>N/A</b>
Minimum Mortar Joint Width:	<b>10mm</b>
Recommended Spacing:	<b>As required</b>

Manufactured by:

**Ancon**<sup>®</sup>  
BUILDING PRODUCTS

**Ancon Building Products**

President Way  
President Park  
Sheffield S4 7UR  
United Kingdom

Tel: +44 (0)114 275 5224  
Fax: +44 (0)114 276 8543  
Email: [info@ancon.co.uk](mailto:info@ancon.co.uk)  
Web: [www.ancon.co.uk](http://www.ancon.co.uk)  
Twitter: @AnconUK

Authorised by:

Stuart Maxwell, Managing Director, on 6th September 2013