

We hereby declare that the product range identified as,

LP21, 125-225mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

Intended Use: **Wall tie for connecting new stone leaf to existing structure via slot channel system.**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity (cavity +15mm): **760N**
Tensile Load Capacity: **5490N**

Capacities given for:

Overall Wall Tie Length: **125mm-225mm**
Design Cavity Width: **Not relevant**
Minimum Embedment Depth: **Not relevant**
Minimum Cover to Face of Wall: **Not relevant**
Minimum Mortar Joint Thickness: **Not relevant**
Minimum Mortar Class: **Not relevant**

Displacement at 1/3 Load Capacity

In compression: **0.12**
In tension: **0.63**

Failure Modes:

In compression: **Bending of tie**
In tension: **Pull-out of tie**

Water shedding capacity: **Not relevant**
Recommended spacing: **As required**

Durability

Material Coating Reference: **3**
Steel Grade: **1.4301/1.4401**

Dangerous Substance **None**

Authorised by:



Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

Leviat
A CRH COMPANY

Ancon Ltd trading as Leviat
President Way
President Park
Sheffield S4 7UR
United Kingdom

+44 (0)114 275 5224
info.ancon.uk@leviat.com
Ancon.co.uk | Leviat.com