

## DECLARATION OF PERFORMANCE

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for UKCA Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



|                            |                    |
|----------------------------|--------------------|
| <b>Declaration Number:</b> | <b>L0351-02-CA</b> |
| <b>Product Type</b>        | <b>SL15</b>        |

|   |  |
|---|--|
| Approved Testing Laboratory   | USW Commercial Services Limited, University of South Wales, Llantwit Road, Treforest, Pontypridd, CF37 1DL |
| Approved Body Number:   | 1679   |
| Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports. |  |
| <b>Intended Use of the Construction Product</b>   |  |
| Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).                |  |

| Essential Characteristics                   | Lintel Length (mm)                                |           |           |
|---|---|-----------|-----------|
|   | 750-1500  | 1501-2100 | 2101-3000 |
| Load Bearing Capacity (kN)                  | 25  | 18        | 15        |
| <i>Figures shown are safe working loads</i> |   |           |           |
| Deflection Under Load                       | Less than Effective Span/325 at safe working load |           |           |
| Water Absorption                            | Zero  |           |           |
| Water Vapour Permeability                   | Not Applicable                                    |           |           |
| Mass per unit area (kg/m <sup>2</sup> )     | 33.9  |           |           |
| Thermal Resistance                          | 17W/mK (Stainless Steel)                          |           |           |
| Resistance to Fire                          | NPD   |           |           |
| Durability (against corrosion)              | Material Coating Reference L3                     |           |           |
| Durability (against freeze/thaw)            | Resistant   |           |           |
| Dangerous Substance                         | None  |           |           |
| Nominal Height (mm)                         | 215   |           |           |
| Mass (kg/m)                                 | 7.29  |           |           |
| Minimum Bearing Length (mm)                 | 150   |           |           |
| Harmonised Technical Specification          | EN 845 - 2: 2013+A1: 2016                         |           |           |

## DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by



---

Rune Magnusson  
Regional Managing Director, UK & Asia  
1st May 2026

Manufactured by:

**Leviat Limited**  
President Way  
President Park  
Sheffield, S4 7UR  
United Kingdom