

DECLARATION OF PERFORMANCE

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for UKCA Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



Declaration Number:	L0355-02-CA
Product Type	SC20

Approved Testing Laboratory	USW Commercial Services Limited, University of South Wales, Llantwit Road, Treforest, Pontypridd, CF37 1DL
Approved Body Number:	1679
Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports.	
Intended Use of the Construction Product	
Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).	

Essential Characteristics	Lintel Length (mm)	
	750-1800	1801-3000
Load Bearing Capacity (kN)	30	20
<i>Figures shown are safe working loads</i>		
Deflection Under Load	Less than Effective Span/325 at safe working load	
Water Absorption	Zero	
Water Vapour Permeability	Not Applicable	
Mass per unit area (kg/m ²)	33.0	
Thermal Resistance	17W/mK (Stainless Steel)	
Resistance to Fire	NPD	
Durability (against corrosion)	Material Coating Reference L3	
Durability (against freeze/thaw)	Resistant	
Dangerous Substance	None	
Nominal Height (mm)	229	
Mass (kg/m)	7.55	
Minimum Bearing Length (mm)	150	
Harmonised Technical Specification	EN 845 - 2: 2013+A1: 2016	

DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by



Rune Magnusson
Regional Managing Director, UK & Asia
1st May 2026

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom