

## **DECLARATION OF PERFORMANCE**

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for UKCA Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



Declaration Number:	L0361-01-CA
Product Type	SW100X

Approved Testing Laboratory	USW Commercial Services Limited, University of South Wales, Llantwit Road, Treforest, Pontypridd, CF37 1DL		
Approved Body Number:	1679		
Performed determination of the product - type on the basis of type testing (based on sampling carried out by the			

Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports.

## Intended Use of the Construction Product

Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).

Essential Characteristics	Lintel Length (mm)								
	750-1500	1501-2100	2101-2700	2701-3600	3601-4800	4801-5400			
Load Bearing Capacity (kN)	29	20	20	51	51	25			
Figures shown are safe working loads		39	39	51	51	35			
Deflection Under Load	Less than Effective Span/325 at safe working load								
Water Absorption	Zero								
Water Vapour Permeability	Not Applicable								
Mass per unit area (kg/m <sup>2</sup> )	57.4	71.8	60.9	73.1	67.5				
Thermal Resistance	17W/mK (Stainless Steel)								
Resistance to Fire	NPD								
Durability (against corrosion)		Material Coating Reference L3							
Durability (against freeze/thaw)	Resistant								
Dangerous Substance	None								
Nominal Height (mm)	143		219		295				
Mass (kg/m)	8.21	10.27	13.34	16.01	19	9.91			
Minimum Bearing Length (mm)	150								
Harmonised Technical Specification	EN 845 - 2: 2013+A1: 2016								



Leviat.com



## **DECLARATION OF PERFORMANCE**

Signed for and on behalf of the manufacturer by

-----

Rune Magnusson Managing Director Europe West & APAC 18<sup>th</sup> August 2022

Manufactured by:

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom



Leviat.com