



Declaration of Performance

Declaration Number:

A0138-00-EN

ANCON hereby declares that the product range identified as,

Briclok A 180mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

Intended Use: **Tie for connecting new masonry to an existing steel column flange. Suitable for 50-80mm cavities.**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity (cavity +15mm): **3280N**
Compressive Load Capacity (design cavity): **3290N**
Tensile Load Capacity: **3300N**

Capacities given for:

Overall Wall Tie Length: **180mm**
Design Cavity Width: **50-80mm**
Minimum Embedment Depth: **Dependent upon application**
Minimum Cover to Face of Wall: **20mm**
Minimum Mortar Joint Thickness: **10mm**
Minimum Mortar Class: **Type M4**

Displacement at 1/3 Load Capacity

In compression: **0.16**
In tension: **NPD**

Failure Modes:

In compression: **Bending of tie**
In tension: **Local deformation of steel around 'Notch'**

Water shedding capacity: **Resistant**
Recommended spacing: **As required**

Durability

Material Coating Reference: **3**
Steel Grade: **1.4301/1.4401**

Dangerous Substance **None**

Authorised by:

Stuart Maxwell, Managing Director, on 12th March 2018 in Sheffield, UK.

Manufactured by:

Ancon[®]

Ancon Ltd
President Way
President Park
Sheffield S4 7UR
United Kingdom

Tel: +44 (0)114 275 5224
Email: info@ancon.co.uk
Web: www.ancon.co.uk