

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SD25 151-300mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

UK CA

Declaration Number:	L0137-04-CA
----------------------------	--------------------

Intended Use:	Wall tie for use with the Ancon 25/14 channel system to connect a masonry leaf to light steel studwork, timber frame or concrete wall through a layer of insulation. See Ancon technical literature for fixing screw references (depending on substrate and insulation depth), and screw/wall tie vertical fixing centres (depending on tie type application).
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	1080N
Tensile Load Capacity (cavity):	1250N
Capacities given for:	
Overall Wall Tie Length:	151-300mm
Design Cavity Width:	110-259mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In Compression:	0.63
In Tension:	0.82
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Pull-out of tie
Water Shedding Capacity:	Resistant
Recommended Spacing:	Refer to Ancon technical literature
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 1st May 2026

Manufactured by;

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom

Declaration Number: L0137-04-CA