Enquiry/Order Form -

CB Coupler Box Reinforcement Continuity Systems

Ancon CB Coupler Boxes utilise the Ancon CARES-approved CXL mechanical rebar connection system.

Please provide product requirements and contact details.

Date On	der Enquiry	Delivery Date			
Company		Delivery Address			
Address					
		Town	Post Code		
Town	Post Code	Contact			
Contact		Tel			
Tel		Project			
Email		Email			
Type U U Bar	Type 2H Two Single Hooks used for boxes wider than 240mm	Type S2 Double Straight Bar			
Type RA Angle (standard in 80mm box)	b Type RA1 Double Angle	b Type RA2 Double Angle	b h l		
Type S Straight Bar	Type H Hook (standard in 80mm box)	Type SH Angle with leg in horizontal plane			

Item	Quantity	ameter (1) Compression Bar (mm)	Stirrup Spacing (mm)	Stirrup Type (see above)	Box Length (2) (mm)	Stirrup Width b (mm)	Stirrup Height h (mm)	ength I (3) Compression Bar (mm)	Stirrup Width c (mm)
-									

- (1) Insert the rebar diameter for both the tension and compression bars.
- (2) To limit the weight and assist installation, the standard box length is 600mm. Other lengths may be possible.
- (3) Insert the required anchorage length for both the tension and compression bars.



