

We hereby declare that the product range identified as,

## YP21, 125-225mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

Intended Use: **Wall tie for use with the Ancon 21/18 Omega channel system to connect a new stone leaf to an existing structure**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom

Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

### Essential Characteristics

Compressive Load Capacity (cavity +15mm): **840N**  
 Tensile Load Capacity: **5490N**

### Capacities given for:

Overall Wall Tie Length: **125mm-225mm**  
 Design Cavity Width: **Not relevant**  
 Minimum Embedment Depth: **Not relevant**  
 Minimum Cover to Face of Wall: **Not relevant**  
 Minimum Mortar Joint Thickness: **Not relevant**  
 Minimum Mortar Class: **Not relevant**

### Displacement at 1/3 Load Capacity

In compression: **0.18**  
 In tension: **0.63**

### Failure Modes:

In compression: **Bending of tie**  
 In tension: **Pull-out of tie**

**Water shedding capacity:** **Not relevant**  
**Recommended spacing:** **As required**

### Durability

Material Coating Reference: **3**  
 Steel Grade: **1.4301/1.4401**

**Dangerous Substance** **None**

Authorised by:

Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

## Leviat

A CRH COMPANY

**Ancon Ltd trading as Leviat**  
 President Way  
 President Park  
 Sheffield S4 7UR  
 United Kingdom

+44 (0)114 275 5224  
 info.ancon.uk@leviat.com  
 Ancon.co.uk | Leviat.com