

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

LPB, 40-225mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0104-00-CE
---------------------	-------------

Intended Use:	Frame cramp for connecting a new stone leaf to an existing structure
Notified Body:	MPA Hannover, Nienburger Str. 3, 30167 Nord, Germany
Notified Body Number:	0764

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	2000N
Tensile Load Capacity:	2970N
Capacities given for:	
Overall Wall Tie Length:	40mm-225mm
Design Cavity Width:	Not relevant
Minimum Embedment Depth:	Not relevant
Minimum Cover to Face of Wall:	Not relevant
Minimum Mortar Joint Thickness:	Not relevant
Minimum Mortar Class:	Not relevant
Displacement at 1/3 Load Capacity	

DECLARATION OF PERFORMANCE

In Compression:	0.14
In Tension:	0.56
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Bending of upstand leg
Water Shedding Capacity:	Not relevant
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



Rune Magnusson
Regional Managing Director, UK & Asia
11th June 2026

Manufactured by;

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom

Declaration Number: L0104-00-CE