

We hereby declare that the product range identified as,

LPL, 125-225mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.

Intended Use: **Wall tie for connecting two new leaves of stone**

Notified Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
 Notified Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity (cavity +15mm): **1140N**
 Tensile Load Capacity: **8690N**

Capacities given for:

Overall Wall Tie Length: **125mm-225mm**
 Design Cavity Width: **Not relevant**
 Minimum Embedment Depth: **Not relevant**
 Minimum Cover to Face of Wall: **Not relevant**
 Minimum Mortar Joint Thickness: **Not relevant**
 Minimum Mortar Class: **Not relevant**

Displacement at 1/3 Load Capacity

In compression: **0.24**
 In tension: **1.01**

Failure Modes:

In compression: **Bending of tie**
 In tension: **Bending of tie at 'L' End**

Water shedding capacity: **Not relevant**
Recommended spacing: **As required**

Durability

Material Coating Reference: **3**
 Steel Grade: **1.4301/1.4401**

Dangerous Substance **None**

Authorised by:

Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

Leviat
 A CRH COMPANY

Ancon Ltd trading as Leviat
 President Way
 President Park
 Sheffield S4 7UR
 United Kingdom

+44 (0)114 275 5224
 info.ancon.uk@leviat.com
 Ancon.co.uk | Leviat.com