

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Ancon Staifix RT2 200mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



| Declaration Number: | L0004-02-CE |
|-----------------------|---|
| | |
| Intended Use: | Type 2 wall tie for connecting two leaves of a cavity wall |
| Notified Body: | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics | | |
|--|---------|--|
| Compressive Load Capacity (cavity +15mm): | 1050N | |
| Compressive Load Capacity (design cavity): | 1300N | |
| Tensile Load Capacity (at min. embedment): | 1800N | |
| Capacities given for: | | |
| Overall Wall Tie Length: | 200mm | |
| Design Cavity Width: | 50-75mm | |
| Minimum Embedment Depth: | 50mm | |
| Minimum Cover to Face of Wall: | 20mm | |
| Minimum Mortar Joint Thickness: | 10mm | |
| Minimum Mortar Class: | Type M2 | |



Declaration Number: L0004-02-CE



DECLARATION OF PERFORMANCE

| Displacement at 1/3 Load Capacity | | |
|-----------------------------------|-----------------------------|--|
| In Compression: | 0.76 | |
| In Tension: | 0.45 | |
| Failure Modes: | | |
| In Compression: | Bending of tie | |
| In Tension: | 5mm displacement | |
| Water Shedding Capacity: | Resistant | |
| Recommended Spacing: | Refer to PD 6697 | |
| Durability | | |
| Material Coating Reference: | 3/23 | |
| Steel Grade: | 1.4301/1.4401/1.4482/1.4597 | |
| Dangerous Substance | None | |

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1st April 2022

Manufactured by:

Leviat Limited

President Way President Park

Sheffield, S4 7UR

United Kingdom

