

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## Ancon ST1 275mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



| Declaration Number:   | L0019-02-CE  |
|-----------------------|--|
|                       |  |
| Intended Use:         | Type 1 wall tie for connecting two leaves of a cavity wall. Suitable for 126-150mm cavities.   |
| Notified Body:        | Technical and Test Institute for Constructions Prague, Branch 0600 -<br>Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020   |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics                  |           |  |
|--|-----------|--|
| Compressive Load Capacity (cavity +15mm):  | 2000N     |  |
| Compressive Load Capacity (design cavity): | 2500N     |  |
| Tensile Load Capacity (at min. embedment): | 2500N     |  |
| Capacities given for:                      |           |  |
| Overall Wall Tie Length:                   | 275mm     |  |
| Design Cavity Width:                       | 126-150mm |  |
| Minimum Embedment Depth:                   | 50mm      |  |
| Minimum Cover to Face of Wall:             | 20mm      |  |
| Minimum Mortar Joint Thickness:            | 10mm      |  |
| Minimum Mortar Class:                      | Type M2   |  |



## Declaration Number: L0019-02-CE



## **DECLARATION OF PERFORMANCE**

| Displacement at 1/3 Load Capacity |                  |  |
|-----------------------------------|------------------|--|
| In Compression:                   | 0.33             |  |
| In Tension:                       | 0.43             |  |
| Failure Modes:                    |                  |  |
| In Compression:                   | Bending of tie   |  |
| In Tension:                       | Pull-out of tie  |  |
| Water Shedding Capacity:          | Resistant        |  |
| Recommended Spacing:              | Refer to PD 6697 |  |
| Durability                        |                  |  |
| Material Coating Reference:       | 3                |  |
| Steel Grade:                      | 1.4301/1.4401    |  |
| Dangerous Substance               | None             |  |

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1<sup>st</sup> April 2022

Manufactured by:

**Leviat Limited** 

President Way President Park

Sheffield, S4 7UR

United Kingdom

