

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## **SPS CJ, 150mm**

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0040-00-CE
Intended Use:	Shear tie for connecting two new leaves of a collar jointed wall.
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	3280N	
Tensile Load Capacity (at min. embedment):	3610N	
Shear Load Capacity:	4340N	
Capacities given for:		
Overall Wall Tie Length:	150mm	
Design Cavity Width:	10mm	
Minimum Embedment Depth:	70mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Type M4	



## Declaration Number: L0040-00-CE



## **DECLARATION OF PERFORMANCE**

Displacement at 1/3 Load Capacity		
In tension:	0.19	
In shear:	1.07	
Failure Modes:		
In compression:	Buckling of tie	
In tension:	Pull out of tie	
In shear:	Rotation of tie	
Recommended Spacing:	As required	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

27<sup>th</sup> July 2023

Manufactured by:

**Leviat Limited** 

President Way

President Park

Sheffield, S4 7UR

United Kingdom

