

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SDB, 226-300mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0026-03-CE
----------------------------	--------------------

Intended Use:	Frame cramp for connecting a new masonry leaf to an existing structure. Suitable for cavities from 170mm to 244mm.
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	2000N
Compressive Load Capacity (design cavity):	3190N
Tensile Load Capacity (cavity):	3460N
Capacities given for:	
Overall Wall Tie Length:	226-300mm
Design Cavity Width:	170-244mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In Compression:	0.87
In Tension:	0.7
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Bending of upstand leg
Water Shedding Capacity:	Resistant
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Managing Director Europe West & APAC
 15th March 2023

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom