

We hereby declare that the product range identified as,

Ancon Staifix RD3 275mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.

Intended Use: **Type 3 wall tie for connecting two leaves of a cavity wall**

Approved Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
 Approved Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Essential Characteristics

Compressive Load Capacity (cavity +15mm): **650N**
 Tensile Load Capacity (at min. embedment): **1100N**

Capacities given for:

Overall Wall Tie Length: **275mm**
 Design Cavity Width: **126-150mm**
 Minimum Embedment Depth: **50mm**
 Minimum Cover to Face of Wall: **20mm**
 Minimum Mortar Joint Thickness: **10mm**
 Minimum Mortar Class: **Type M2**

Displacement at 1/3 Load Capacity

In compression: **0.30**
 In tension: **0.18**

Failure Modes:

In compression: **Bending of tie**
 In tension: **5mm displacement**

Water shedding capacity: **Resistant**
Recommended spacing: **Refer to PD 6697**

Durability

Material Coating Reference: **3/23**
 Steel Grade: **1.4301/1.4401/1.4482**

Dangerous Substance **None**

Authorised by:

Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

Leviat
 A CRH COMPANY

Ancon Ltd trading as Leviat
 President Way
 President Park
 Sheffield S4 7UR
 United Kingdom

+44 (0)114 275 5224
 info.ancon.uk@leviat.com
 Ancon.co.uk | Leviat.com