

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Ancon Staifix STF6 75mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0051-01-NI
Intended Use:	Type 6 wall tie for connecting a masonry outer leaf to a structural timber frame. Suitable for 75mm cavity.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	640N	
Compressive Load Capacity (design cavity):	510N	
Tensile Load Capacity (at min. embedment):	920N	
Capacities given for:		
Overall Wall Tie Length:	152mm	
Design Cavity Width:	75mm	
Minimum Embedment Depth:	77mm	
Minimum Cover to Face of Wall:	20mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Type M2	





DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity		
In Compression:	0.43	
In Tension:	0.99	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Straightening of tie	
Water Shedding Capacity:	Resistant	
Recommended Spacing:	Refer to Table B.1. BS 5268-6.1:1996	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1st April 2022

Manufactured by:

Leviat Limited

President Way President Park

Sheffield, S4 7UR

United Kingdom

