

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

TFMT7

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0055-00-CE
---------------------	-------------

Intended Use:	Type 7 wall tie for connecting a masonry outer leaf to structural timber frame. Suitable for cavities from 50mm to 150mm.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	1690N
Compressive Load Capacity (design cavity):	1690N
Tensile Load Capacity:	1810N
Movement Tolerant:	Up to 30mm max. to accommodate shrinkage of timber frame
Capacities given for:	
Overall Wall Tie Length:	200m
Design Cavity Width:	150mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm

DECLARATION OF PERFORMANCE

Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2
Displacement at 1/3 Load Capacity	
In compression:	0.61
In tension:	1.31
Failure Modes:	
In compression:	Bending of tie
In tension:	5mm displacement
Water shedding capacity:	Resistant
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 15th July 2025

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom