

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

AMR/G/D3.5/W100

conforms to the provisions of EN 845-1:2013+A1:2016, as Bed Joint Reinforcement defined in 4.2.2 of the Standard.

CE

| Declaration Number: L0226-02-CE |
|---------------------------------|
|---------------------------------|

| Intended Use: | For structural use in walls and partitions |
|-----------------------|--|
| Notified Body: | Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic |
| Notified Body Number: | 1020 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Product Dimensions | | |
|--|----------------------|--|
| Length: | 2700 ±1.5% | |
| Width: | 100 ±5mm | |
| Profile Height: | 2.9 ±0.4mm | |
| Longitudinal Wire Size: | 3.93 ±0.1mm | |
| Cross Wire Size: | 2.30 ±0.1mm | |
| Pitch of Cross Wires: | 450 ±3.0% | |
| Performance | | |
| Characteristic Yield Strength of Longitudinal Wires: | 500N/mm ² | |
| Characteristic Yield Strength of Cross Wires: | 500N/mm ² | |
| Bond Strength: | 3250N | |



Leviat.com



DECLARATION OF PERFORMANCE

| Bond Length: | 450mm | |
|-------------------------------|----------------------|--|
| Anchorage Length: | 450mm | |
| Shear Load Capacity of Welds: | 2500N | |
| Mortar Class: | General purpose ≥ M4 | |
| Masonry Units: | fb ≥ 5 N/mm² | |
| Ductility: | Normal | |
| Durability | | |
| Material Coating Reference: | R13 Galvanised Steel | |
| Dangerous Substances: | None | |

Signed for and on behalf of the manufacturer by

Rune Magnusson Managing Director Europe West & APAC 3rd March 2023

Manufactured by:

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom

