

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

CCB-L-200

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

**UK
CA**

Declaration Number:	L0147-02-CA
---------------------	--------------------

Intended Use:	Shear tie for connecting cellular clay thin-joint blockwork to an existing structure.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Shear Load Capacity:	690N
Capacities given for:	
Overall Wall Tie Length:	130mm
Minimum Mortar Joint Thickness:	1mm
Minimum Mortar Class:	Wienerberger Zero Plus
Displacement at 1/3 Load Capacity	
In shear:	0.34
Failure Modes:	
In shear:	Bending of tie

DECLARATION OF PERFORMANCE

Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



Rune Magnusson
Regional Managing Director, UK & Asia
1st May 2026

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom

Declaration Number: L0147-02-CA