

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## CCB-SMJ-200

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.



Declaration Number:	L0148-01-CA
Intended Use:	Shear tie for connecting cellular clay thin-joint blockwork to an existing structure whilst allowing in-plane movement.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Shear Load Capacity:	280N	
Capacities given for:		
Overall Wall Tie Length:	95mm	
Minimum Mortar Joint Thickness:	1mm	
Minimum Mortar Class:	Wienerberger Zero Plus	
Displacement at 1/3 Load Capacity		
In shear:	1.06	
Failure Modes:		
In shear:	Deformation of tie	





## **DECLARATION OF PERFORMANCE**

Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1<sup>st</sup> April 2022

Manufactured by:

**Leviat Limited** 

President Way President Park Sheffield, S4 7UR United Kingdom

