

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SDB T2, 325-450mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

**UK
CA**

| | |
|----------------------------|--------------------|
| Declaration Number: | L0153-03-CA |
|----------------------------|--------------------|

| | |
|-----------------------|--|
| Intended Use: | Frame cramp for connecting a new masonry leaf to an existing structure. Suitable for cavities from 245mm to 394mm. |
| Approved Body: | Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom |
| Approved Body Number: | 1289 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

| Essential Characteristics | |
|---|---|
| Compressive Load Capacity (cavity +15mm): | 1720N |
| Tensile Load Capacity (cavity): | 4730N |
| Capacities given for: | |
| Overall Wall Tie Length: | 325mm-450mm |
| Design Cavity Width: | 245mm-394mm |
| Minimum Embedment Depth: | “B” End Not relevant/ ‘S’ End 50mm |
| Minimum Cover to Face of Wall: | 20mm |
| Minimum Mortar Joint Thickness: | 10mm |
| Minimum Mortar Class: | Type M2 |
| Displacement at 1/3 Load Capacity | |

DECLARATION OF PERFORMANCE

| | |
|---------------------------------|------------------------|
| In Compression: | 0.18 |
| In Tension: | 0.47 |
| Failure Modes: | |
| In Compression: | Bending of tie |
| In Tension: | Bending of upstand leg |
| Water Shedding Capacity: | Resistant |
| Recommended Spacing: | As required |
| Durability | |
| Material Coating Reference: | 3 |
| Steel Grade: | 1.4301/1.4401 |
| Dangerous Substance | None |

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 1st May 2026

Manufactured by;

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom

Declaration Number: 10153-03-CA