

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

SDB T1, 325-450mm

CE

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Asymmetrical Wall Tie.

Declaration Number:	L0151-01-CE
Intended Use:	Frame cramp for connecting a new masonry leaf to an existing

Intended Use:	Frame cramp for connecting a new masonry leaf to an existing structure. Suitable for cavities from 245mm to 394mm.
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	2610N	
Tensile Load Capacity (cavity):	5460N	
Capacities given for:		
Overall Wall Tie Length:	325mm-450mm	
Design Cavity Width:	245mm-394mm	
Minimum Embedment Depth:	"B' End Not relevant/ 'S' End 50mm	
Minimum Cover to Face of Wall:	20mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Туре М2	
Displacement at 1/3 Load Capacity		



Leviat.com



DECLARATION OF PERFORMANCE

In Compression:	1.76	
In Tension:	0.85	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Bending of upstand leg	
Water Shedding Capacity:	Resistant	
Recommended Spacing:	As required	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson Managing Director Europe West & APAC 15th March 2023

Manufactured by;

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom



Leviat.com