

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## Ancon Staifix HRD4 250mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.

## 

Declaration Number: L0133-01-NI
---------------------------------

Intended Use:	Type 4 wall tie for connecting two leaves of a cavity wall.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	350N	
Tensile Load Capacity (at min embedment):	650N	
Capacities given for:		
Overall Wall Tie Length:	250mm	
Design Cavity Width:	101-125mm	
Minimum Embedment Depth:	50mm	
Minimum Cover to Face of Wall:	20mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Type M2	
Displacement at 1/3 Load Capacity		



Leviat.com



## **DECLARATION OF PERFORMANCE**

In Compression:	0.13	
In Tension:	0.66	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Straightening of tie	
Water Shedding Capacity:	Resistant	
Recommended Spacing:	Refer to PD 6697	
Durability		
Material Coating Reference:	3/23	
Steel Grade:	1.4301/1.4401/1.4597	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

\_\_\_\_\_ \_\_\_\_\_

Rune Magnusson Managing Director Europe West & APAC 1<sup>st</sup> April 2022

Manufactured by;

Leviat Limited President Way President Park Sheffield, S4 7UR United Kingdom

