

DECLARATION OF PERFORMANCE

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



| Declaration Number: | L0314-00-CE |
|---------------------|-------------|
| Product Type | SU90 |

| Approved Testing Laboratory | SKG-IKOB Certificatie B.V., Poppenbouwing 56 4191 NZ, Geldermalsen, Netherlands |
|-----------------------------|---|
| Approved Body Number: | 0960 (ex - 0957) |

Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports.

Intended Use of the Construction Product

Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).

| Face and all Olerandon delications | Lintel Length (mm) | | |
|--------------------------------------|--------------------|----------------------------|-------------|
| Essential Characteristics | 900-1800 | 1801-2100 | 2101-2400 |
| Load Bearing Capacity (kN) | | | |
| Load Ratio 1:1 and 19:1 | 32 | 48 | 45 |
| Figures shown are safe working loads | | | |
| Deflection Under Load | Less than Eff | ective Span/325 at safe we | orking load |
| Water Absorption | | Zero | |
| Water Vapour Permeability | | Not Applicable | |
| Mass per unit area (kg/m²) | 78.4 | 94 | l.2 |
| Thermal Resistance | 1 | 7W/mK (Stainless Steel) | |
| Resistance to Fire | | NPD | |
| Durability (against corrosion) | Mat | erial Coating Reference L | 3 |
| Durability (against freeze/thaw) | | Resistant | |
| Dangerous Substance | | None | |
| Nominal Height (mm) | 157 | 1: | 57 |

| Nominal Height (mm) | 157 | 157 |
|-----------------------------------|-------|------------------------|
| Mass (kg/m) | 12.31 | 14.79 |
| Minimum Bearing Length (mm) | | 150 |
| Harmaniand Tankning Charification | | 1945 2: 2012: 14: 2016 |

|--|





DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

18th August 2022

Manufactured by:

Leviat Limited

President Way President Park Sheffield, S4 7UR

United Kingdom



