

## DECLARATION OF PERFORMANCE

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



|                            |                    |
|----------------------------|--------------------|
| <b>Declaration Number:</b> | <b>L0327-01-CE</b> |
| <b>Product Type</b>        | <b>SUX150</b>      |

|   |   |
|---|---|
| Approved Testing Laboratory   | SKG-IKOB Certificatie B.V., Poppenbouwing 56 4191 NZ, Geldermalsen, Netherlands |
| Approved Body Number:   | 0960 (ex - 0957)  |
| Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports. |   |
| <b>Intended Use of the Construction Product</b>   |   |
| Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).                |   |

| Essential Characteristics                   | Lintel Length (mm)                                       |           |              |           |
|---|--|-----------|--------------|-----------|
|   | 900-2700   | 2701-3000 | 3001-3900    | 3901-4800 |
| Load Bearing Capacity (kN)                  | <b>60</b>  | <b>55</b> | <b>50</b>    | <b>32</b> |
| Load Ratio 1:1 and 19:1                     |  |           |              |           |
| <i>Figures shown are safe working loads</i> |  |           |              |           |
| Deflection Under Load                       | <b>Less than Effective Span/325 at safe working load</b> |           |              |           |
| Water Absorption                            | <b>Zero</b>  |           |              |           |
| Water Vapour Permeability                   | <b>Not Applicable</b>                                    |           |              |           |
| Mass per unit area (kg/m <sup>2</sup> )     | <b>83.3</b>  |           | <b>97.1</b>  |           |
| Thermal Resistance                          | <b>17W/mK (Stainless Steel)</b>                          |           |              |           |
| Resistance to Fire                          | <b>NPD</b>   |           |              |           |
| Durability (against corrosion)              | <b>Material Coating Reference L3</b>                     |           |              |           |
| Durability (against freeze/thaw)            | <b>Resistant</b>   |           |              |           |
| Dangerous Substance                         | <b>None</b>  |           |              |           |
| Nominal Height (mm)                         | <b>231</b>   |           |              |           |
| Mass (kg/m)                                 | <b>19.25</b>   |           | <b>22.42</b> |           |
| Minimum Bearing Length (mm)                 | <b>150</b>   |           |              |           |
| Harmonised Technical Specification          | <b>EN 845 - 2: 2013+A1: 2016</b>                         |           |              |           |

## DECLARATION OF PERFORMANCE

Signed for and on behalf of the manufacturer by



-----  
Rune Magnusson  
Regional Managing Director, UK & Asia  
1st May 2026

Manufactured by:

**Leviat Limited**  
President Way  
President Park  
Sheffield, S4 7UR  
United Kingdom

Declaration Number: L0327-01-CE