

## **DECLARATION OF PERFORMANCE**

We hereby declare that in compliance with the Construction Products Regulation (EU) No. 305/2011, that the stainless steel lintels listed below are manufactured according to the requirements of the Harmonised Standard EN 845-2:2013+A1:2016 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2:2013+A1:2016.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 (System 3 of Assessment and Verification of Constancy of Performance).



Declaration Number:	L0347-00-CE
Product Type	SL4

Approved Testing Laboratory	SKG-IKOB Certificatie B.V., Poppenbouwing 56 4191 NZ, Geldermalsen, Netherlands
Approved Body Number:	0960 (ex - 0957)

Performed determination of the product - type on the basis of type testing (based on sampling carried out by the manufacturer) and issued test reports.

## **Intended Use of the Construction Product**

Lintels to be used in walls and partitions (to support loads over openings in masonry walls with a semi - structural role in the works).

Essential Characteristics	Lintel Length (mm)
	900-1200
Load Bearing Capacity (kN)	4
Figures shown are safe working loads	
Deflection Under Load	Less than Effective Span/325 at safe working load
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Mass per unit area (kg/m²)	31.7
Thermal Resistance	17W/mK (Stainless Steel)
Resistance to Fire	NPD
Durability (against corrosion)	Material Coating Reference L3
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Nominal Height (mm)	88
Mass (kg/m)	2.79
Minimum Bearing Length (mm)	150
Harmonised Technical Specification	EN 845 - 2: 2013+A1: 2016





## **DECLARATION OF PERFORMANCE**

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

18<sup>th</sup> August 2022

Manufactured by:

**Leviat Limited** 

President Way

President Park

Sheffield, S4 7UR

United Kingdom

