

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Ancon Staifix HRD4 275mm

conforms to the provisions of, ZA Annex, EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0134-01-CE
----------------------------	--------------------

Intended Use:	Type 4 wall tie for connecting two leaves of a cavity wall.
Notified Body:	Technical and Test Institute for Constructions Prague, Branch 0600 - Brno, Hněvkovského 77, 617 00 Brno - Komárov, Czech Republic
Notified Body Number:	1020

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	350N
Tensile Load Capacity (at min embedment):	650N
Capacities given for:	
Overall Wall Tie Length:	275mm
Design Cavity Width:	126-156mm
Minimum Embedment Depth:	50mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2
Displacement at 1/3 Load Capacity	

DECLARATION OF PERFORMANCE

In Compression:	0.13
In Tension:	0.3
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Straightening of tie
Water Shedding Capacity:	Resistant
Recommended Spacing:	Refer to PD 6697
Durability	
Material Coating Reference:	3/23
Steel Grade:	1.4301/1.4401/1.4597
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Managing Director, UK & Asia
 1st May 2026

Manufactured by;

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom

Declaration Number: 10134-01-CE