

## **DECLARATION OF PERFORMANCE**

We hereby declare that the product range identified as,

## Ancon ST1 275mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0019-01-CA
Intended Use:	Type 1 wall tie for connecting two leaves of a cavity wall. Suitable for 126-150mm cavities.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics		
Compressive Load Capacity (cavity +15mm):	2000N	
Compressive Load Capacity (design cavity):	2500N	
Tensile Load Capacity (at min. embedment):	2500N	
Capacities given for:		
Overall Wall Tie Length:	275mm	
Design Cavity Width:	126-150mm	
Minimum Embedment Depth:	50mm	
Minimum Cover to Face of Wall:	20mm	
Minimum Mortar Joint Thickness:	10mm	
Minimum Mortar Class:	Type M2	



## Declaration Number: L0019-01-CA



## **DECLARATION OF PERFORMANCE**

Displacement at 1/3 Load Capacity		
In Compression:	0.33	
In Tension:	0.43	
Failure Modes:		
In Compression:	Bending of tie	
In Tension:	Pull-out of tie	
Water Shedding Capacity:	Resistant	
Recommended Spacing:	Refer to PD 6697	
Durability		
Material Coating Reference:	3	
Steel Grade:	1.4301/1.4401	
Dangerous Substance	None	

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1<sup>st</sup> April 2022

Manufactured by:

**Leviat Limited** 

President Way President Park

o wood

Sheffield, S4 7UR

United Kingdom

