

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

DT 250mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.

**UK
CA**

| | |
|----------------------------|--------------------|
| Declaration Number: | L0046-03-CA |
|----------------------------|--------------------|

| | |
|-----------------------|---|
| Intended Use: | Type 3 wall tie for connecting two leaves of a cavity wall. |
| Approved Body: | Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom |
| Approved Body Number: | 1289 |

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

| Essential Characteristics | |
|---|------------------|
| Compressive Load Capacity (cavity +15mm): | 910N |
| Tensile Load Capacity (at min embedment): | 2370N |
| Capacities given for: | |
| Overall Wall Tie Length: | 250mm |
| Design Cavity Width: | 101-125mm |
| Minimum Embedment Depth: | 50mm |
| Minimum Cover to Face of Wall: | 20mm |
| Minimum Mortar Joint Thickness: | 10mm |
| Minimum Mortar Class: | Type M2 |
| Displacement at 1/3 Load Capacity | |

DECLARATION OF PERFORMANCE

| | |
|---------------------------------|----------------------|
| In Compression: | 0.12 |
| In Tension: | 0.39 |
| Failure Modes: | |
| In Compression: | Bending of tie |
| In Tension: | Straightening of tie |
| Water Shedding Capacity: | Resistant |
| Recommended Spacing: | Refer to PD 6697 |
| Durability | |
| Material Coating Reference: | 3 |
| Steel Grade: | 1.4301/1.4401/1.4597 |
| Dangerous Substance | None |

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 1st May 2026

Manufactured by;

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom

Declaration Number: 10046-03-CA