

Declaration Number: A0022-01-EN

Declaration of Performance

ANCON hereby declares that the product range identified as,

SD1, 225/250mm

conforms to the provisions of,

ZA Annex, EN 845-1: 2003 +A1: 2008

as a

Symmetrical Wall Tie covered in clause 1 of the standard

Intended Use: Type 1 wall tie for connecting two leaves of a cavity wall.

Suitable for 76-125mm cavities. Type 1 in M2 (iv) mortar

only.

Notified Body: Lucideon

Queens Road, Penkhull

STOKE-ON-TRENT ST4 7LQ

United Kingdom

Tel: +44 (0)1782 764444

Notified Body Number: 1289

This product conforms to **System 3 -** Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics

Compressive Load Capacity: 3190N (M2 (iv) Mortar)
Tensile Load Capacity: 2820N (M2 (iv) Mortar)

Water Shedding Capability: Resistant

Durability: Material/coating reference 3, Steel grade 1.4301

Dangerous Substances: None

Conditions

Embedment Depth: min. 62.5mm

Minimum Mortar Class: Type M2 (iv)

Minimum Mortar Joint Width: 10mm

> quee 0

Recommended Spacing: Refer to Clause 6.2.2.2. PD 6697:2010

Manufactured by:

Ancon BUILDING PRODUCTS

Ancon Building Products President Way President Park Sheffield S4 7UR United Kingdom

Tel: +44 (0)114 275 5224 Fax: +44 (0)114 276 8543 Email: info@ancon.co.uk Web: www.ancon.co.uk Twitter: @AnconUK Authorised by:

Stuart Maxwell, Managing Director, on 16th May 2013, in Sheffield, UK.