

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Two-Part Tie, 300mm-400mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

**UK
CA**

Declaration Number:	L0049-02-CA
----------------------------	--------------------

Intended Use:	Type 2 wall tie for connecting two leaves of a cavity wall. Suitable for 300-400mm cavities. [Max. 170mm inner section].
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	1420N
Compressive Load Capacity (design cavity):	1090N
Tensile Load Capacity (at min. embedment):	2700N
Capacities given for:	
Overall Wall Tie Length:	550mm
Design Cavity Width:	400mm max
Minimum Embedment Depth:	75mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In Compression:	0.43
In Tension:	0.61
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Pull-out of tie
Water Shedding Capacity:	Resistant
Recommended Spacing:	Refer to PD 6697
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



 Rune Magnusson
 Regional Managing Director, UK & Asia
 1st May 2026

Manufactured by:

Leviat Limited
 President Way
 President Park
 Sheffield, S4 7UR
 United Kingdom