

## DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

### Two-Part Tie, 150-300mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

**UK  
CA**

<b>Declaration Number:</b>	<b>L0048-02-CA</b>
----------------------------	--------------------

Intended Use:	Type 2 wall tie for connecting two leaves of a cavity wall. Suitable for 150-300mm cavities. [Max. 170mm inner section].
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

<b>Essential Characteristics</b>	
Compressive Load Capacity (cavity +15mm):	<b>1330N</b>
Compressive Load Capacity (design cavity):	<b>1710N</b>
Tensile Load Capacity (at min. embedment):	<b>2700N</b>
<b>Capacities given for:</b>	
Overall Wall Tie Length:	<b>450mm</b>
Design Cavity Width:	<b>300mm max</b>
Minimum Embedment Depth:	<b>75mm</b>
Minimum Cover to Face of Wall:	<b>20mm</b>
Minimum Mortar Joint Thickness:	<b>10mm</b>
Minimum Mortar Class:	<b>Type M2</b>

## DECLARATION OF PERFORMANCE

<b>Displacement at 1/3 Load Capacity</b>	
In Compression:	0.41
In Tension:	0.61
<b>Failure Modes:</b>	
In Compression:	Bending of tie
In Tension:	Pull-out of tie
<b>Water Shedding Capacity:</b>	Resistant
<b>Recommended Spacing:</b>	Refer to PD 6697
<b>Durability</b>	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
<b>Dangerous Substance</b>	None

Signed for and on behalf of the manufacturer by



-----  
 Rune Magnusson  
 Regional Managing Director, UK & Asia  
 1st May 2026

Manufactured by:

**Leviat Limited**  
 President Way  
 President Park  
 Sheffield, S4 7UR  
 United Kingdom