

We hereby declare that the product range identified as,

# Ancon Staifix RD3 275mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.

Intended Use: **Type 3 wall tie for connecting two leaves of a cavity wall**

Approved Body: Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom  
Approved Body Number: 1289

This product conforms to **System 3** - Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

## Essential Characteristics

Compressive Load Capacity (cavity +15mm): **650N**  
Tensile Load Capacity (at min. embedment): **1100N**

## Capacities given for:

Overall Wall Tie Length: **275mm**  
Design Cavity Width: **126-150mm**  
Minimum Embedment Depth: **50mm**  
Minimum Cover to Face of Wall: **20mm**  
Minimum Mortar Joint Thickness: **10mm**  
Minimum Mortar Class: **Type M2**

## Displacement at 1/3 Load Capacity

In compression: **0.30**  
In tension: **0.18**

## Failure Modes:

In compression: **Bending of tie**  
In tension: **5mm displacement**

**Water shedding capacity:** **Resistant**  
**Recommended spacing:** **Refer to PD 6697**

## Durability

Material Coating Reference: **3/23**  
Steel Grade: **1.4301/1.4401/1.4482**

**Dangerous Substance** **None**

Authorised by:



Peter McDermott, Managing Director Europe West & APAC, on 1st January 2021 in Sheffield, UK.

Manufactured by Leviat

**Leviat**  
A CRH COMPANY

Ancon Ltd trading as Leviat  
President Way  
President Park  
Sheffield S4 7UR  
United Kingdom

+44 (0)114 275 5224  
info.ancon.uk@leviat.com  
Ancon.co.uk | Leviat.com