

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

Ancon Staifix TIM6

comprising: 175mm, 200mm, 225mm, 250mm

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as an Asymmetrical Wall Tie.

UK CA

Declaration Number:	L0054-04-CA
---------------------	-------------

Intended Use:	Type 6 wall tie for connecting a masonry outer leaf to a structural timber frame. Suitable for cavities from 50mm to 150mm.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above approved body.

Essential Characteristics	
Compressive Load Capacity (cavity +15mm):	610N
Tensile Load Capacity (at min. embedment):	900N

Capacities given for:	
Overall Wall Tie Length:	175mm, 200mm, 225mm, 250mm
Design Cavity Width:	50-75mm, 76-100mm, 101-125mm, 126-150mm
Minimum Embedment Depth:	Timber 30mm/Masonry 60mm
Minimum Cover to Face of Wall:	20mm
Minimum Mortar Joint Thickness:	10mm
Minimum Mortar Class:	Type M2

DECLARATION OF PERFORMANCE

Displacement at 1/3 Load Capacity	
In Compression:	0.22
In Tension:	0.81
Failure Modes:	
In Compression:	Bending of tie
In Tension:	Pull-out of tie
Water Shedding Capacity:	Resistant
Recommended Spacing:	Refer to Table B.1. BS 5268-6.1:1996
Durability	
Material Coating Reference:	3
Steel Grade:	1.4567
Dangerous Substance	None

Signed for and on behalf of the manufacturer by



Rune Magnusson
Regional Managing Director, UK & Asia
21st October 2026

Manufactured by:

Leviat Limited
President Way
President Park
Sheffield, S4 7UR
United Kingdom

Declaration Number: L0054-04-CA