

DECLARATION OF PERFORMANCE

We hereby declare that the product range identified as,

CCB-IWJ-180

conforms to the provisions of, ZA Annex, BS EN 845-1:2013+A1:2016 as a Symmetrical Wall Tie.



Declaration Number:	L0060-01-CA
Intended Use:	Wall tie for connecting two cellular clay thin-joint blockwork walls at 90 degrees.
Approved Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, United Kingdom
Approved Body Number:	1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance. All necessary testing was conducted at the above notified body.

Essential Characteristics	
Shear Load Capacity:	930N
Capacities given for:	
Overall Wall Tie Length:	180mm
Design Cavity Width:	Not relevant
Minimum Embedment Depth:	90mm
Minimum Mortar Joint Thickness:	1mm
Minimum Mortar Class:	Wienerberger Zero Plus
Displacement at 1/3 Load Capacity	
In shear:	0.26





DECLARATION OF PERFORMANCE

Failure Modes:	
In shear:	Deformation of tie
Recommended Spacing:	As required
Durability	
Material Coating Reference:	3
Steel Grade:	1.4301/1.4401
Dangerous Substance	None

Signed for and on behalf of the manufacturer by

Rune Magnusson

Managing Director Europe West & APAC

1st April 2022

Manufactured by:

Leviat Limited

President Way

President Park

Sheffield, S4 7UR

United Kingdom

